

TO WHOM IT MAY CONCERN:

Notification of Non-dangerous Goods
Based on the UN Recommendation

Product: Panasonic Sealed Lead-Acid Batteries

This notification refers to treat Sealed Lead-Acid Battery described above as non-dangerous goods for transportation by boat and/or air. After our own test, we judge this battery is satisfied with the special provisions 238 added UN No. 2800 as given below. Also this battery is satisfied with the special provisions A 67 prescribed in DANGEROUS GOODS REGULATIONS by IATA.

[UN2800 SPECIAL PROVISIONS 238]

Batteries can be considered as non-spillable provided that they are protected against short circuits, are securely packaged and are capable of withstanding the vibration and pressure differential tests given below, without leakage of battery fluid.

Vibration test: The battery is rigidly clamped to the platform of a vibration machine and a simple harmonic motion having an amplitude of 0.8mm (1.6mm maximum total excursion) is applied. The frequency is varied at the rate of 1 Hz/min between the limits of 10 Hz to 55 Hz. The entire range of frequencies and return is traversed in 95 +/- 5 minutes for each mounting position (direction of vibration) of the battery. The battery must be tested in three mutually perpendicular positions (to include testing with fill openings and vents, if any, in an inverted position) for equal time periods.

Pressure differential test: Following the vibration test, the battery is stored for six hours at 24°C +/- 4°C while subjected to a pressure differential of at least 88 kPa. The battery must be tested in three

mutually perpendicular positions (to include testing with fill openings and vents, if any, in an inverted position) for at least six hours in each position.

Note: Non-spillable type batteries which are an integral part of and necessary for the operation of mechanical or electronic equipment are exempt the requirements of this packing instruction provided they are securely fastened in the battery holder on the equipment and protected in such a manner as to prevent damage and short circuits.

Non-spillable batteries are not subject to these Recommendations if, at a temperature of 55°C, the electrolyte will not flow from a ruptured or cracked case and there is no free liquid to flow and if, when packaged for transport, the terminals are protected from short circuit.

Note: This notification is only described for transportation of Sealed Lead-Acid batteries. Therefore this notification is free from specification and/or drawing of Sealed Lead-Acid batteries.

Matsushita Battery Industrial Co., Ltd.
Storage Battery Division
Issued No.9803

Signature: *Nobuyuki Aoki*
Name: Nobuyuki Aoki
Total: Senior Engineer
Date: Apr.16 1998

Panasonic
Industrial Europe GmbH
Postfach 540849
22508 Hamburg
Winsbergring 15
22525 Hamburg